

Reineckea 100 吉祥草100

产品规格 Specification:

输入电压: AC220V, 内置开关电源, 输出24V, PF>0.7
 额定功率: 120W (64W@220V 50Hz 25°C典型双色
 瞬时功率)
 灯具效率: 非线性成像光路, 整灯发光效能>31lm/W.
 光源类型: 48颗3瓦灯珠, 650mA驱动, 最大2010流明。
 光源颜色: 青草的真实颜色-黄色嫩绿色浅绿色白等混合
 光场(10%)角: 标准8°, 光束有各个方向和长度随机
 组合可控制
 控制信号: 符合WH/T 32—2008 DMX512-A标准, Arm内
 核MCU输出32位精度调光, PWM>1.5KHz, 摄像无频闪
 调光曲线: 内置Dim0-Dim4 5种调光曲线, 低DMX数值
 调光平滑, 无跳闪, 无视觉冲击
 控制模式: 自走/主从模式, 亮度可调, 效果速度可调
 通道: 8CH, 总亮度, 颜色1, 2, 3, 4, 效果组合、
 速度、调光曲线
 显示: 按键控制屏幕, LED显示可自动关闭, 自动显示
 DMX信号正常与否, 显示屏硅胶配备遮光板
 外壳材料: 6063拉伸铝, 标准哑光银色, 可定制阳极氧
 化其他颜色, 可配备单片挡光板
 安规等级: 电气II级, 输入3*2.5mm2 黑色橡胶线(VDE,
 CCC), 防火V-1, 防护IP65
 工作温度: -20~+45°C, 外壳最高温度50°C@25°C环境
 认证类别: 产品通过CE, RoHS, 电源通过CQC,
 UL60950, UL8750等
 绝缘参数: 抗电强度1.5KV, 阻抗强度 > 2 MΩ
 净重: 11KG, 含3mm厚度钣金支撑架
 尺寸: 766*108*213mm (头部垂直放置时)


Voltage input: AC220V, output 24V PF>0.7.
 Rated Power: 120W (64W@25°C Typical double color output)
 Luminaire Efficiency: Nonlinear imaging, Light Efficacy >31lm/W.
 LED Lumens: 48 PCS 3W LED, 650mA Driving, Max 2010 lumens
 LED Color: yellow, peak green, reseda Purewhite combination.
 Could Customized other.
 Field Angle(10%): standard 8°, light beam long and short
 combination adjustable.
 Control signal: Meet E1.11 - 2004 USITT DMX512-A, 32 bit,
 PWM>1.5KHz, Video flicker free.
 Dimming Curve: Dim 4 square law dimming, smooth in low
 DMX Value dimming, not Jumping, no vision shock
 Control mode: DMX/stand alone/master and slave.
 Chanel option: 8CH, Dimmer, Color 1, 2, 3, 4, build-in chase,
 peed, dimming Curve.
 Housing material: 6063 Extrusion Aluminium, standard
 Matte silver, single barndoor available.
 Safty: CClass II, 3C 2.5mm2 VDE cable, Flame Rating V-1,
 Protect Rated IP65.
 Operate temperature: -20~+45°C, Lampbody peak
 temperature 50°C@25°C Environment
 Certificated: Product pass CE, RoHS, SMPS pass CQC or
 UL60950, UL8750.
 Insulated: Dielectric strength 1.5KV, Impedance strength > 2MΩ
 Weight: 11KG, with side-install supporting bracket.
 Size: 766*108*213mm (Including standard bracket,
 could customize sliding block)

产品特色 Features:

自然仿生学, 动态草舞效果, 颜色贴近自然
 仿生春草, 稻谷等在风中摇摆, 呈现各种季节状态下的原野景色
 嫩绿为春, 绿色为夏, 黄色为秋, 白色为冬
 洗墙式应用, 可照射墙面, 桥面, 可斜向投射, 建筑内部投射等
 偏配光非线性成像, 光束颜色和速度可调, 可拼接
 DMX512信号控制, 自走、主从机控制, 多机互联控制, 4按钮地址码设置led显示屏
 LED显示可自动关闭, 自动显示DMX信号正常与否
 内置Dim4曲线调光从0-100%, 调光频率600Hz, 拍照无闪烁
 内置温度控制功能, 当LED工作过热时, 智能降低LED的输出功率, 15000小时产品寿命
 Simulated grasss swaying effect with grass original color.
 Simulation of grass dancing in the wind, show all season colors of grass field.
 Show Grassfield effect in all nature mode and human affection
 Grass swaying effect, wash wall direction use, grass leaf all direction, color and speed adjustable, could connect.
 DMX512 signal control, 4 buttons address setting with LED screen.
 Display could auto turn off after no operation, show DMX signal situation make tesing easier.
 Dim 4 Square law dimming for 0-100%, video flicker free, with strobe/gradual change/color change inbuilt programs;
 NTC temperature control system inside, MCU reduce the power output when LED working temperature is too high,
 15000 Hours Longevity.

优点:

- 使用非线性光学成像技术
- 无需工地重新对焦, 避免漏水风险
- 又是一年芳草绿, 依然十里杏花红。--中国春联
- 迎得春光先到来, 浅黄轻绿映楼台。
只缘袅娜多情思, 便被春风长倩猜。--刘禹锡



The Element Series

美丽中国系列 Reineckea 100 吉祥草100 (可定制开发)

