

# Rainbow Nt9 彩虹NT9

## 产品规格 Specification:

输入电压:AC100-240VAC,47-63 Hz  
 输出:12V DC,功率因素>0.7  
 额定功率: 40W,典型消耗功率32W/220V  
 最大光输出:730流明, 整灯效率: 24lm/W  
 轴向最大光强: 2263Cd  
 LED颜色: 红色625nm,绿色525nm,蓝色455nm  
 控制信号: 符合WH/T 32-2008 DMX512-A标准,  
 32位精度调光, 低DMX数值调光平滑,无视觉冲击  
 通道数: 3CH,4CH, 5CH, 8CH  
 显示板: 触摸屏, LED显示, 2分钟不操作可关闭,  
 自动显示DMX信号正常与否  
 调光性能: 内置Dim0-Dim4 5种调光曲线, 平滑调光  
 PWM频率: >1.5KHz, 快速频闪>12次每秒满载/空载切换  
 光场角(10%强度): 120\*20°, 可配备挡光板  
 外壳材质:压铸铝, 防护等级IP65  
 散热方式: 自然散热, 内置NTC高温保护功能  
 接头和配线: 配备不锈钢线扣和IP67防水公母头  
 外壳颜色:标准哑光黑色,  
 可定制南瓜色PANTONE哑光150U  
 焊接工艺: 180°C低温回流焊接, 高达15000小时的  
 开关电源与主板寿命  
 产品尺寸: L\*W\*H=270\*166\*284mm  
 质量: 5.2 Kg, 含双提手重量  
 工作温度范围: -20°C - +55°C  
 认证类别: CE,Rohs

Power input:AC 100-240VAC,47-63 Hz, Output:12VDC,  
 Power Factor>0.7  
 Rated Power: 40W,Typical Consumption 32W/220V  
 Total Light Output 730Lumens,Luminaire Efficiency 24lm/W  
 Peak Intensity: 2263Cd  
 LED Color: R=625nm,G=525nm,B=455nm  
 Control signal:Meet E1.11 - 2004 USITT DMX512-A, 32 bit  
 precise dimming, smooth in low DMX Value dimming,  
 no vision shock. Channels:3CH,4CH, 5CH,8CH  
 Display:Touch operation,LED display show DMX situation and  
 auto turn off when no operation  
 Dimming: with Dim0-Dim4 5 dimming curve, smooth dimming  
 PWM frequency:>1500Hz,Flash Rate Endurance Full Load:>12Hz  
 Full load/void load flash  
 Beam Angles Optional:120\*20°, barndoor available  
 Housing material: Die cast aluminum,Protection Rated IP65  
 Cooling Method:Neutral Heasink,Thermal protection:  
 NTC overheat protection  
 Connectors and Cables:IP67 Cable locker,and Male/Female  
 connectors. Housing color:Standard Matte Black, could  
 customized Pumkin color PANTONE 150U  
 Soldering technology: 180°CReflow Soldering,makesure 15000  
 hours Longevity for SMPS and mainboard  
 Size: L\*W\*H=270\*166\*284mm. Weight: 5.2 Kg, with double yoke.  
 Operating temperature: -20°C - +55°C  
 Certificated:CE, Rohs


## 产品特点 Features:

模拟直线型彩虹, 投射红橙黄绿青蓝紫几种并列的颜色  
 自然元素、南瓜颜色与外观  
 长条形光斑, 适合透射于建筑表面和地面小径等  
 标准光束角(10%强度) 120\*20° 度配置, 彩虹真彩色。  
 专利外观设计, 为南瓜形状仿生, 回归自然感觉, 和人性化。  
 取消了容易损坏的按键面板, 使用触摸屏控制板, 2分钟无操作LED显示屏自动关闭  
 显示板自动显示DMX信号到达与否, 便利安装调试, 提供DIM0-DIM4共5种调光曲线。  
 配备透气阀, 内外气压平衡, 玻璃面内部变热时无雾气  
 Linear shape Rainbow, RAYGCB Paralle Color  
 Natural Pumkin color and looking  
 suitable for buiding facade, Garden Path application  
 Field angle (10% intensity) 120\*20° degree standard, Genius Rainbow.  
 Patent new lamp body, Amitaion of pumkin design, appears nature and sincere.  
 Touch LED display, no easy broken buttons, 2minutes no operation no display  
 LED Display board shows DMX signal, offer Dimming curve squarelaw Dim4  
 With waterproof air valve to balance pressure, get rid of mosiusture on glass innerface.

## 优点

- 使用非线性光学成像技术
- 无需工地重新对焦, 避免漏水风险
- 安得五彩虹, 驾天作长桥。——李白
- 晚虹斜日塞天昏, 一半山川带雨痕。——雍陶
- 雨霁彩虹卧, 半夜水明楼。——赵善括

**Ledmewish**  
 缔朗照明



The Element Series  
 美丽中国系列  
**Rainbow Nt9**  
**彩虹NT9**  
 (可定制开发)

