

Parco Zoom Penta B 全能变焦帕科B

产品规格 Specification:

输入电压: AC 90-240V 47-63Hz, PF:>0.9
输出电压: DC24V, 15000小时开关电源使用寿命
额定功率: 120W (典型值96W@220V 50Hz), 耐受快速频闪>12次每秒满载与空载切换
灯具效率: 36颗*3W, 700mA驱动, 全开总3340流明输出, 整灯发光效能>35.2lm/W.混色等级: 舞台级混色, 标准色品方差SDC<0.005, Ra>90, R9>80, 优良显色性
光源色品: 红色625nm8颗, 绿色525nm10颗, 蓝色460nm6颗, 琥珀色595nm6颗, 正白6000K6颗。
光场(10%)角: 最小8°, 最大52° 中间角度使用步进电机可调, 轴向最大光强: 81500Cd. 控制信号: DMX512, 32位精度调光, 低DMX数值调光柔滑, 无跳闪, 无视觉冲击控制模式: 符合WH/T 32-2008 DMX512-A/主从模式, 可手动调色调角度. 无线模式: 2.4GHz, 兼容瑞典DMX和国产LM-DMXA0可由菜单选择
调光: 内置Dim0-Dim4 5种调光曲线, PWM>1500Hz, 摄像无频闪. 显示板: 触摸屏幕, LED显示, 2分钟无操作可关闭, 自动显示DMX信号状态
外壳材料: 压铸铝ADC12, 标准哑光黑色, 可定制南瓜色/哑光白色. 散热方式: 自然散热, 内置NTC高温保护功能
接头与电线: 输入与PowerCON TRUE1 Chassis兼容, 可串接, 信号使用IP65级3XLR连接座
焊接工艺: 180°C低温回流焊接, 高达15000小时的开关电源与主板寿命
参考配件: 挡光板, 挂钩, 和保险绳, 电源转换线
工作温度: -20~+55°C, LED灯板最高温度80°C
安规等级: 电气I级, 抗电强度1.5KV, 绝缘电阻>2 MΩ, 防火V-1, 防护IP65
认证类别: 产品通过CE, RoHS, 电源通过CQC, UL60950, UI8750等. 净重: 5.6Kg, 含3mm厚度折弯钣金双支撑架
尺寸: L*W*H=270*166*284mm

Input voltage: AC 90-240V 47-63Hz, PF>0.9
Output voltage: DC24V, SMPS longevity 15000Hours
Rated Power: 120W (Typ.96W@220V 50Hz), Flash Rate Endurance>12Hz Full/void load. Luminaire Efficiency: 36pcs3W 700mA Driving, Full on 3340 Lumens, Efficacy >35.2lm/W.
Color Evenness: Performance Class, Standard deviation of Chromaticity SDC<0.005, Ra>90, R9>80. LED Color: Red625nm (8PCS), Green525nm(10PCS), Blue460nm(6PCS), Amber595nm (6pcs), White6000K(6PCS). Field Angle(10%): Min8°, Max52°, Step Moto Zooming, max intensity 81500Cd. Control signal: DMX, 32 bit Dim 4 square law dimming, smooth in low DMX Value dimming, no vision shock. Control mode: Meet E1.11 - 2004 USITT DMX512-A/Master could set Color and beam angle on display board
Wireless Details: 2.4GHz, Could choose W-DMX and LM-DMXA0 on display board. Dimming Curve: Dim0-4 Curve optional, PWM>1500Hz, video flicker free. Display: Touch operation, LED display show DMX situation and aotu turn off when no operation
Housing material: Die cast ADC12, standard Matte black, could customized Pumpkin color. Cooling Method: Neutral Heatsink, Thermal protection: NTC overheat protection
Soukect: Power same as PowerCON TRUE1 Chassis, Signal with IP65 3XLR Both daisy chain. Soldering technology: 180°C Reflow Soldering, makesure 15000 hours Longevity for SMPS and mainboard
Accessories: Power adaptor Cable as standard, Barndoor, Hook, Safty Cable available. Operate temperature: -20~+55°C, Light board peak temperature 80°C, intelligent control. Safty: Class II, Flame Rating V-1, Protect Rated Ip65. Certificated: Product pass CE, RoHS, SMPS pass CQC or UL60950, UI8750. Weight: 5.6KG, with double yokes 3mm thick supporting bracket. Size: L*W*H=270*166*284mm


产品特点 Features:

RGBAW混色均匀, 可实现多种颜色和色温, 并优化白光的显色性指标到最优。
专利外观设计, 为南瓜形状仿生, 回归自然感觉, 和人性化。
步进电机线性变焦, DMX控制, 光束角度8-52°, 适用各种投射距离
3340流明输出, 52度°下10%光场角内流明数量占比90%以上
取消了容易损坏的按键面板, 使用触摸屏控制板, 2分钟无操作LED显示屏自动关闭
显示板自动显示DMX信号状态, 便利安装调试, 提供双版本2.4GHz无线传输。
出光面采用防雾工艺, 内部发热时无雾气, 外壳配备透气阀, 达到内外气压平衡
灯珠和元器件均采用贴片和低温回流焊接工艺, 保证导热充分, 性能稳定, 寿命长
RGBAW Color mixing to achieve even color and tunable white, to optimize Ra and R9.
Patent new lamp body, Amifaion of pumpkin design, appears nature and sincere.
Step moto DMX control linear Zooming, field Angle 8-52°, suitable for all kinds of height install.
3340 Lumens Output, output 90% Lumens within 10% Intensity at 52°.
Touch LED display, no easy broken buttons, 2 minutes no operation no display
LED Display board to shows DMX condiction, offer 2 versions 2.4GHz Wireless DMX.
Innner Glass surface is processed as condensation-free, also with waterproof air valve to balance pressure.
Use SMT and low temperature reflow soldering tech to make sure heat conduct and heat sink.

优点

- 全能型角度变焦和混色体验
- 满足了户外租赁演出功能, 适用于多种安装高度
- 满足了建筑景观多角度、多颜色、多色温试灯和使用

Ledmewish
缔朗照明



Zoom Parcan

变焦系列

Parco Zoom Penta B
全能变焦帕科B

