

Keen Film 50 锐意50

产品规格 Specification:

输入电压: AC100-240V, 输出12VDC, PF>0.7
 额定功率: 65W (25°C典型满载瞬时功率54W)
 光学效果: 线性成像光路, 可旋转图案投射, 可定制单色和多色玻璃图案盘
 光源亮度: 1颗Lumiled白光LED, 8A驱动, 标准1680流明输出, 整灯发光效能>41lm/W.
 光源色温: 标准6000K, 可定制色温, 定制GOBO片可自带颜色
 光场(10%): 角: 标配全范围12° -40°, 带手动精准调焦
 控制信号: 符合WH/T 32-2008 DMX512-A标准, Arm内核MCU输出32位精度调光, PWM>1.5KHz, 摄像无频闪调光曲线: 内置Dim0-Dim4 5种调光曲线, 低DMX数值调光平滑, 无跳闪, 无视觉冲击
 控制模式: 自走/主从模式, 亮度可调, 效果速度可调
 通道: 6CH, 亮度, 颜色、速度、方向、频闪、调光曲线, 可选择5CH
 显示: 触摸控制屏幕, LED显示可自动关闭, 自动显示DMX信号正常与否
 外壳材料: 压铸铝ADC12, 标准哑光喷粉黑色, 可定制喷漆白色, 可配备挡光板
 安规等级: 电气I级, 输入3*2.5mm2黑色橡胶线(VDE, CCC), 防火V-1, 防护IP66, 配备透气阀平衡内外气压
 工作温度: -20~+45°C, 外壳最高温度60°C@25°C环境下
 认证类别: 产品通过CE, RoHS, 电源通过CQC, UL60950, UL8750等
 绝缘参数: 抗电强度1.5KV, 阻抗强度 > 2MΩ
 净重: 5.7KG, 含3mm厚度折弯钣金双支撑架
 尺寸: 429*265*286mm(水平向前照射)

Voltage input: AC100-240V, Output 12VDC, PF>0.7
 Rated Power: 65W (54W@25°C Peak output)
 Optical Technology: Linear Image, rotating GOBO, customized multi color GOBO
 LED Lumens: 1pcs* Lumiled White color LED 8A Driving, total 1680 Lumens, Light Efficacy >41lm/W.
 LED CCT: Standard 6000K, could customized other CCT while Gobo have their own color
 Field Angle(10%): Comprehensive 12° -40° hand adjustable
 Control signal: DMX512, 32 bit ARM MCU, PWM>1.5KHz, Video flicker free.
 Dimming Curve: Dim 4 square law dimming, smooth in low DMX Value dimming, not Jumping, no vision shock
 Control mode: Meet E1.11 - 2004 USITT DMX512-A/stand alone/master and slave, effect speed and brightness adjustable.
 Chanel option: 6CH, Dimmer, Color, Clockwise and convert, Speed, Shutter, dimming Curve, could choose 5CH.
 Housing material: Die cast aluminum ADC12, standard Matte black, customized glossy White painting, barn door available.
 Safty: Class II, 3C 2.5mm2 VDE cable, Flame Rating V-1, Protect Rated IP66 with Vent.
 Operate temperature: -20~+45°C, Lamp body peak temperature 60°C@25°C Environment
 Certificated: Product pass CE, RoHS, SMPS pass CQC or UL60950, UL8750.
 Insulated: Dielectric strength 1.5KV, Impedance strength > 2MΩ
 Weight: 5.7KG, with double yokes 3mm thick supporting bracket.
 Size: 429*265*286mm (Horizontal spot direction)

产品特色 Features:

动态图案投射, 可单色, 可多色, 清晰成像, 可定制GOGO片
 内置图案方向调整和旋转
 标配12° -40° 光斑, 适合多种距离投射, 现场精准对焦不影响防水性能
 Lumiled LED灯珠, 低功耗, 性能稳定, 寿命长, 高亮度, 1680流明输出
 DMX512信号控制, 自走、主从机控制, 多机互联控制, 触摸设置LED显示屏
 LED显示可自动关闭, 自动显示DMX信号正常与否
 内置Dim4曲线调光从0-100%, 调光频率1.5KHz, 拍照无闪烁
 内置温度控制功能, 当LED工作过热时, 智能降低LED的输出功率, 15000小时产品寿命
 配备透气阀, 内外气压平衡, 玻璃面内部受热时无雾气


Dynamic Gobo profile, clear image, single or multi-color, could customized goboGOGOs.
 Built-in MOTO to adjust GOBO direction, and rotatable.
 12° -40° Beam Angle Available by manual focusing, not affecting IP Rated.
 Lumiled LED, 1680 Lumens Output, Low consume, stable performance, long longevity.
 DMX512 signal control, touch setting with LED screen.
 Display could auto turn off after no operation, show DMX signal situation make testing easier.
 Dim 4 Square law dimming, video flicker free, with strobe/gradual change in built programs;
 NTC temperature control system inside, reduce the power output when LED working temperature is too high.
 With waterproof air vent to balance pressure, get rid of moisture on glass innerface.

优点

- 使用线性光学成像技术, 内置图案片精准定位和可变旋转功能
- 可根据投射距离使用伸缩筒手动对焦, 宽角度可调, 无漏水风险
- 适用于“福”字, 窗棂图案等自带方向图案
- 大尺寸GOBO片, 适用于投射“山水画”级别矢量图
- 清晰的成像光斑, 提供cdr文件格式图案需求可快速定制图案
- 可定制双色, 多色及3D效果GOBO片



Ledmewish
 缔朗照明



The Painting Series

丹青系列

Keen Film 50
 锐意50

